

Figure 1 (Prior Art)




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16 Prior Art




Figure 17 Prior Art




Figure 18




Figure 19




Figure 20




Figure 21




Figure 22




Figure 23




Figure 24




Figure 25




Figure 26




Figure 27




Figure 28




Figure 29




Figure 30




Figure 31




Figure 32




Figure 33




Figure 34




Figure 35




Figure 36




Figure 37




Figure 38




Figure 39




Figure 40




Figure 41




Figure 42




Figure 43




Figure 44




Figure 45

Monitor Point	Frequency	Std Pkg		New Pkg.		Shield Effectiveness	
		E	H	E	H	E	H
	GHz	dBV/m	dBA/m	dBV/m	dBA/m	dB	dB
+Z	0.9	-2	-21	-12	-42	10	21
+Z	2.4	7	-22	-4	-42	11	20
+Z	5.2	13	-22	5	-41	8	19
+Z	10.0	16	-19	11	-39	5	20

Fig. 46

Semiconductor Chip	Die Size	Material	Power Dissipation
Daughter Die 1	1.8x0.9x0.2mm	Silicon	100mW
Daughter Die 2	2.1x1.1x0.2mm	Gallium Arsenide	1W
Mother Die 3	2.65x2.65x0.2mm	Glass-Quartz	100mW

Fig. 47

Monitor Point	Standard Package	New Package
	Temp (deg C)	Temp (deg C)
Daughter Die 2	137	116
% Improvement	-	22

Fig. 48